



- · Electronic Intensity Stabilizer ensures consistent performance. Beam strength will not weaken between charges!
- · Instant-on operation; lamp reaches full power immediately
- · Portable and rugged. Anodized aluminum lamp body minimizes corrosion and stands up to years of heavy use.
- Powered by a rechargeable NiMH battery. Provides 90 minutes of continuous inspection between charges.

| MODEL | NOMINAL STEADY-STATE UV-A INTENSITY at 15 in (38 cm) ① | UV-A COVERAGE AREA at 15 in (38 cm) at minimum 1,000 μW/cm² | VISIBLE LIGHT MEASUREMENT |
|---------|---|--|------------------------------|
| OPX-365 | 18,000 μW/cm ² | 3 in (7.6 cm) Diameter | <2 foot-candles (22 lux) |

Light Source: UV-A (365 nm) Lamp Style: Cordless flashlight Lamp Head Diameter: 2 in (5.1 cm) Length: 8 in (20.3 cm) Weight: 11.8 oz (335 g) (with Battery) 3.6V, 2.0 Ah NiMH internal Power Requirements: battery stick (rechargeable) Run Time: 90 minutes (continuous) **Charge Time:** 4 hours

Series meter, and is factory set to the value shown.






Comes complete with OPTIMAX™ 365 (365 nm) lamp, smart AC and DC chargers, UV-absorbing spectacles, belt holder and hard carrying case. AC charger available in 120V, 230V, 240V or 100V versions.






UV-A Beam Profiles



Surface Contour Profile at 15 in (38 cm)




-0.5 (-1.5)

0 (0)

1 (2.5) 1.5

2 (5)





-1.5 -1 -0.5 0 (-4) (-2.5) (-1.5) (0) 0.5 1 (1.5) (2.5) 1.5 (4)

X-inches (cm)

www.Spectro-UV.com 4 Dubon Ct., Farmingdale, NY 11735 866-230-7305